

102670

OrbitalPRO 4CCT Black

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt black finish
- Constructed from die cast aluminium alloy & steel
- Fire rated to 30, 60 & 90 minutes
- Tested with insulation cover thickness 270mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65
- No visible light source
- Fits into shallow spaces
- Anti-glare indirect light source creating a stylish clean look

SPEC DATA

Product Wattage:	9W
Product Lumen:	460
Lumen/W:	51
Kelvin:	2700/3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	130°
Power Factor:	0.9
Driver Type:	Constant Current 200mA
Inrush Current at Start Up:	2.1A
Energy Rating:	F
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.302
Cut-out (mm):	Ø97mm
Minimum Cavity Depth (mm):	45mm
Terminal Block:	3 way Quick fit
Class:	2

ACCESSORIES

108097, EM kit standard & self test 2-in-1

