


# Constant Voltage TRIAC Dimming LED Driver

## Features:

- Dimmable with leading edge or trailing edge dimmer
- Independent compact design
- Protections: opencircuit, shortcircuit, overload, overtemperature
- SELV equivalent
- Protection class II
- Smooth dimmable compatible with most dimmer
- Dimming range 1...100%



## Parameters:

| Model No. | Input voltage (V) | Output voltage (V) | Output current (A) | Power factor (λ) | Ambient temperature ta (°C) | Max. casing temperature tc (°C) | Type of light source for which it is intended | Efficiency full load (%) | No-load power (Pno in W) | Standby power (Psb in W) | Suit for dimming (Y/N) | Networked standby power (Pnet in W) | For OLED and HL Maxmium output power (W) | Max. output (W) | Dimensions LxWxH (mm) | Weight (g) |
|-----------|-------------------|--------------------|--------------------|------------------|-----------------------------|---------------------------------|---|--------------------------|--------------------------|--------------------------|------------------------|-------------------------------------|--|-----------------|-----------------------|------------|
| 79332     | 220-240           | 24                 | 0.1-1.04           | 0.95             | -20...+50                   | 70                              | LED   | 85                       | N/A                      | N/A                      | Y                      | N/A                                 | N/A                                      | 25              | 128x52x30             | 110        |
| 79333     | 220-240           | 24                 | 0.5-2.08           | 0.95             | -20...+50                   | 70                              | LED   | 86                       | N/A                      | N/A                      | Y                      | N/A                                 | N/A                                      | 50              | 184x61x32             | 240        |
| 79334     | 220-240           | 24                 | 1.4-4.2            | 0.95             | -20...+45                   | 80                              | LED   | 91                       | N/A                      | N/A                      | Y                      | N/A                                 | N/A                                      | 100             | 210x67x34             | 360        |