

91513

LALO 3000K

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white & clear acrylic finish
- Constructed from aluminium alloy & acrylic
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- Flicker free
- IP44

SPEC DATA

| | |
|-----------------------------|------------------------|
| Product Wattage: | 4W |
| Product Lumen: | 240 |
| Lumen/W: | 60 |
| Kelvin: | 3000K |
| SDCM: | 6 |
| CRI: | 80 |
| Dimmable: | N |
| Lifetime (Hours): | 30000 |
| Beam Angle: | 45° |
| Power Factor: | 0.5 |
| Driver Type: | Constant Current 300mA |
| Inrush Current at Start Up: | 100mA |
| Energy Rating: | G |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 2 |
| Operating Temp.: | -20 to 50 Degree |
| Product Weight (KG): | 0.09 |
| Cut-out (mm): | Ø35mm |
| Minimum Cavity Depth (mm): | 24mm |
| Terminal Block: | 2 way |
| Class: | 2 |

ACCESSORIES

- 91944, Emergency LED conversion kit self test
- 92514, Emergency LED conversion kit
- 92519, LALO dimmable driver accessory
- 101339, EM conversation self test

