

101342

ShieldECO CCT Anti-glare

FEATURES

- 3 years (2 years + 1 year) extended warranty
- Matt white & clear acrylic finish
- Constructed from steel & acrylic
- Fire rated to 30, 60 & 90 minutes
- Tested with insulation cover thickness 270mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65

SPEC DATA

Product Wattage:	5W
Product Lumen:	520
Lumen/W:	104
Kelvin:	3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	60°
Power Factor:	0.9
Driver Type:	Constant Current 85mA
Inrush Current at Start Up:	Max. 20A
Energy Rating:	E
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	2
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.188
Cut-out (mm):	Ø80mm
Minimum Cavity Depth (mm):	80mm
Terminal Block:	4-way quick fit
Class:	2

ACCESSORIES

- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge
- 103944, EM conversion kit 8W

