## 103940

# Saxby HeroPRO XL CCT Microwave Emergency

#### **FEATURES**

- 5 years (2 years + 3 years) extended warranty
- · Matt white textured & opal PC finish
- · Constructed from polycarbonate
- Complete with built in microwave sensor
- Battery warranty 5 years (Based on working temperature 0 - 45°)
- 3 hours emergency maintained & non-maintained fitting
- IP65
- IK08
- · Fast fit hinged gear tray

#### **SPEC DATA**

Product Wattage: 20/24/28W Product Lumen: 2000/2400/2800Lm

Lumen/W: 100 2W EM Wattage: EM Lumen: 190

Kelvin: 3000/4000/6000K

Energy Rating: D Dimmable: No 120° Beam Angle: Power Factor: > 0.9CRI: >80 Lifetime (Hours): 50000 LED Brand: **EVERLIGHT** 

SDCM:

Driver Type: Constant Current 145mA

200mA Inrush Current at Start Up: Product Voltage: 220-240V 50/60 Surge Protection (KV): 3.75

Operating Temp.: -20 to 40 Degree

LiFePO4 3.2V 1500mAh x 1pc Battery:

Product Weight (KG): Terminal Block: 5-way fast fix

Class:

### **MICROWAVE MOVEMENT SENSOR DATA**

Operating Voltage: 220 ~ 240Vac Hertz: 50/60

Rated Load: 400W (Capacitive load) 800W (Resistive load)

Stand-by Power:

Sensitivity: Ceiling Height 3m: 100% / 75% / 50% / 25% / 10%

Ceiling Height 6m: 100% / 75% / 50% Wall Height 2m: 100% / 75% / 50% / 25% / 10%

5s / 30s / 90s / 3min / 20min / 30min 2Lux / 10Lux / 25Lux / 50Lux / Disable

Microwave Frequency:  $5.8~\mathrm{GHz}~\pm75\mathrm{MHz}$ Transmitting Power: 1mW Max.


Detection Range: Ceiling Height 3m: 3-6m (radius)


Wall Height 1.5-2m: 12-15m

Detection Angle: 360° (Ceiling) / 120° (Wall)

Working Temperature:  $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ 









Hold-time:

Daylight Sensor: