

108763

## ShieldLITE 5W

### FEATURES

- 3 years (2 years + 1 year) extended warranty
- White & clear acrylic finish
- Constructed from polycarbonate & acrylic
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65 – Front and back

### SPEC DATA

Product wattage:	5W
Product Lumen:	520
Lumen/W:	104
Kelvin:	2700/3000/4000/6000K
Energy Rating:	D
Dimmable:	Yes
Beam Angle:	60°
Power Factor:	0.5
CRI:	80
Lifetime (Hours):	30000
LED Type:	SMD
SDCM:	6
Driver Type:	Constant current 65mA
Inrush Current at Start Up:	10A
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Cut out:	Ø50mm
Minimum Cavity Depth:	60mm
Operating Temp:	-20 to 40 Degree
Product Weight (KG):	0.87
Terminal Block:	2-way
Class:	2

### ACCESSORIES

- 95202, ShieldECO satin bezel
- 95203, ShieldECO chrome bezel
- 95204, ShieldECO black bezel
- 78419, ShieldECO antique brass bezel

