

120334

## Lunaro 3-Phase 4000K White

### FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white finish
- Constructed from die cast aluminium alloy
- Adjustable
- 350° rotation and 90° tilt
- Max. wattage 32W
- RAL Colour: 9003

### SPEC DATA

|                             |                                                                    |
|-----------------------------|--------------------------------------------------------------------|
| Product Wattage:            | 12W/14W/16W/18W/20W/22W/<br>24W/26W/28W/30W/32W                    |
| Product Lumen:              | 1220/1390/1580/1750/1950/2110/<br>2600/2770/2930/3150/3260         |
| Lumen/W:                    | 102                                                                |
| Kelvin:                     | 4000K                                                              |
| Energy Rating:              | D                                                                  |
| Dimmable:                   | No                                                                 |
| Beam Angle:                 | 38°                                                                |
| Power Factor:               | 0.9                                                                |
| SDCM:                       | 3                                                                  |
| CRI:                        | 90                                                                 |
| Lifetime (Hours):           | 50000                                                              |
| LED Brand:                  | Bridgelux Inc                                                      |
| Driver Type:                | Constant current 300/350/400/450/<br>500/550/600/650/700/750/800mA |
| Inrush Current at Start Up: | 16A                                                                |
| Driver Out Voltage:         | 36V                                                                |
| Product Voltage:            | 220-240V                                                           |
| Hertz:                      | 50/60                                                              |
| Surge Protection (KV):      | 1.5                                                                |
| Operating Temp.:            | -20 to 40 Degree                                                   |
| Product Weight (KG):        | 0.5                                                                |
| Class:                      | 2                                                                  |

