

72181

# Slimline Luik CCT Microwave Emergency Gear Tray

## FEATURES

- 5 years (2 years + 3 years) extended warranty
- Complete with built in microwave sensor
- 3 hours emergency maintained fitting
- Battery warranty 5 years (Based on working temperature 0 - 45°)

## SPEC DATA

Product Wattage:	9/14/18W
Product Lumen:	2500
Lumen/W:	138
Kelvin:	3000/4000/6000K
Energy Rating:	D
Dimmable:	No
Beam Angle:	120°
Power Factor:	>0.7
CRI:	>80
Lifetime (Hours):	50000
LED Brand:	Intematix
SDCM:	6
Driver Type:	Constant Current 180mA
Inrush Current at Start Up:	200mA
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1
Operating Temp.:	-20 to 40 Degree
Battery:	LiFePO4 3.2V 1500mAh x 1pc
Product Weight (KG):	0.695
Terminal Block:	4-way fast fix
Class:	1
EM Wattage / Lumen with Plain Casing:	2W / 220Lm
EM Wattage / Lumen with Eyelid Casing:	2W / 158Lm
EM Wattage / Lumen with Grill Casing:	2W / 196Lm

## MICROWAVE MOVEMENT SENSOR DATA

Operating Voltage:	220 ~ 240Vac
Hertz:	50/60
Rated Load:	400W (Capacitive load) 800W (Resistive load)
Stand-by Power:	≤ 0.5W
Sensitivity:	Ceiling Height 3m: 100% / 75% / 50% / 25% / 10% Ceiling Height 6m: 100% / 75% / 50% Wall Height 2m: 100% / 75% / 50% / 25% / 10%
Hold-time:	5s / 30s / 90s / 3min / 20min / 30min
Daylight Sensor:	2Lux / 10Lux / 25Lux / 50Lux / Disable
Microwave Frequency:	5.8 GHz ± 75MHz
Transmitting Power:	1mW Max.
Detection Range:	Ceiling Height 3m: 3-6m (radius) Wall Height 1.5-2m: 12-15m
Detection Angle:	360° (Ceiling) / 120° (Wall)
Working Temperature:	-20°C ~ 60°C

