

90376

ShieldPro CCT

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white & clear acrylic finish (white bezel included)
- Constructed from steel & aluminium alloy & polycarbonate
- CCT switchable - Three colour temperature to choose from: Warm White (3000K), Cool White (4000K) & Daylight White (6000K)
- Loop-in / Loop-out detachable quick wire push-fit connector
- 30, 60 and 90 minutes fire rated
- Tested with insulation cover thickness 27cm
- IP65. Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD

SPEC DATA

Product Wattage:	7W
Product Lumen:	800
Lumen/W:	114
Kelvin:	3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	60°
Power Factor:	0.9
Driver Type:	Constant Current 120mA
Energy Rating:	F
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
IK Rating:	08
Product Weight (KG):	0.2485
Cut-out (mm):	Ø70mm
Minimum Cavity Depth (mm):	57mm
Terminal Block:	Push-fit 6 ways
Class:	2

ACCESSORIES

- 90377, Satin nickel bezel
- 90378, Polished chrome bezel
- 92513, Matt black bezel

