


# Constant Voltage 24V LED Driver

## Features:

- Independent compact design
- Protections: opencircuit, shortcircuit, overload, overtemperature
- Simple installation
- SELV equivalent
- Protection class II
- Non-Dimmable



## Parameters:

| Model No. | Input voltage (V) | Output voltage (V) | Output current (A) | Power factor (λ) | Ambient temperature ta (°C) | Max. casing temperature tc (°C) | Type of light source for which it is intended | Efficiency full load (%) | No-load power (Pno in W) | Standby power (Psb in W) | Suit for dimming (Y/N) | Networked standby power (Pnet in W) | For OLED and HL Maximum output power (W) | Max. output (W) | Dimensions LxWxH (mm) | Weight (g) |
|-----------|-------------------|--------------------|--------------------|------------------|-----------------------------|---------------------------------|---|--------------------------|--------------------------|--------------------------|------------------------|-------------------------------------|--|-----------------|-----------------------|------------|
| 79682     | 220-240           | 24                 | 0-0.83             | 0.80             | -20...+50                   | 80                              | LED   | 83                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 20              | 113x44x28             | 100        |
| 79328     | 220-240           | 24                 | 0-1.7              | 0.95             | -20...+50                   | 85                              | LED   | 86                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 40              | 166x52x24             | 140        |
| 79329     | 220-240           | 24                 | 0-0.31             | 0.95             | -20...+50                   | 85                              | LED   | 89                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 75              | 184x61x32             | 270        |
| 79681     | 220-240           | 24                 | 0-6.25             | 0.95             | -20...+45                   | 85                              | LED   | 91                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 150             | 210x67x34             | 320        |
| 98992     | 220-240           | 24                 | 0-0.25             | 0.55C            | -20...+50                   | 80                              | LED   | 78                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 6               | 81x39x22              | 50         |
| 98993     | 220-240           | 24                 | 0-0.50             | 0.80C            | -20...+50                   | 80                              | LED   | 82                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 12              | 98x39x22              | 100        |
| 98994     | 220-240           | 24                 | 0-2.1              | 0.95             | -20...+50                   | 85                              | LED   | 87                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 50              | 184x61x32             | 270        |
| 98995     | 220-240           | 24                 | 0-2.5              | 0.95             | -20...+50                   | 85                              | LED   | 89                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 60              | 184x61x32             | 270        |
| 98996     | 220-240           | 24                 | 0-4.2              | 0.95             | -20...+50                   | 85                              | LED   | 92                       | N/A                      | N/A                      | N                      | N/A                                 | N/A                                      | 100             | 184x61x32             | 300        |